

## U1P-Bike - 4T Full Synthetic Motor Oil

# 10W-40 API SN, JASO MA2 WITH ESTER

Motorcycle – ATV | United States

### Product Description

U1P-BIKE SAE 10W-40 Full Synthetic 4T API SN JASO MA2 Engine Oils with Ester are full synthetic, super high-performance, multi-grade lubricants for use in high-RPM, 4-stroke motorcycle engines with integral gear boxes and wet clutches as well as for use in any application requiring a four-stroke engine oil meeting the requirements of JASO MA2, JASO MA or API SN. Blended with 100% synthetic base stocks, synthetic esters, and premium performance additives U1P-Ride Full Synthetic 4T Engine Oils with Ester provide excellent protection during rapid RPM increase. Specialty friction modifiers provide for smooth clutch and gear shift operation while specialty antioxidants and sophisticated dispersant technology provide enhanced cleanliness. U1P-BIKE Full Synthetic Engine Oils 4T (Four-Stroke) are highly shear stable therefore eliminating viscosity breakdown. These products are full synthetic multi-grade engine oils suitable for use in all seasons.



### Features and Benefits

- For all 4-stroke motorcycles and ATVs with or without catalytic converters.
- For engines with or without integrated gear box, transmission. Wet or dry clutch.
- JASO MA2 API SN ensures optimum clutch performance at start-up, acceleration, and full speed.
- Exceptional wear protection extending engine, gear box and clutch life, leading to reduced maintenance cost.
- Ester Technology improves engine response.
- Improved high temperature deposit protection for engine cleanliness and minimum sludge build up.
- Reduces oil thickening facilitating extended oil life, inside the manufacturer's oil change interval recommendation.
- Smoother shifting and enhanced clutch feeling and precision.



## Product Code

Presentation	SKU	Manufacture ID	UPC
Quart	UFS10404TESNMA2L	UL414	810050652704
5 Gallon Pail	UFS10404TESNMA2P	UL414	810050652681
55 Gallon Drum	UFS10404TESNMA2D	UL414	810050652674
265 Gallon Tote	UFS10404TESNMA2T	UL414	810050652667

## This product meets or exceeds the requirements of

API SN  
JASO MA2

## Properties and Specifications\*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	90.65
Viscosity @ 100°C, cSt, ASTM D445	15.0
Viscosity index, ASTM D2270	175
CCS Apparent Viscosity, cP, ASTM D5293	5,500@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	20,000@-30°C
Pour point, °C, ASTM D97	-40
Flash point, °C, ASTM D92	210

\*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023